

# PYROWIN® CWB

## Fire protection cavity wall boxes



### Winning with the WIN series – even if there's a fire

Always airtight, always smoke-tight: With our PYROWIN® CWB fire protection cavity wall boxes, fire protection measures can be created reliably in fire-resistant lightweight walls with metal substructures.

You will also benefit from all the WIN series advantages, such as labelled cable and pipe entries, triple screw domes and tear protection. Effective fire protection made easy!

### All advantages at a glance

- Tested to European standards and approved for fire resistant classes EI90/EI120
- Noise impact insulation to DIN EN ISO 10140 and DIN EN ISO 717-1, sound-proofing value of 70 dB
- Halogen-free
- Facing installation possible horizontally or vertically
- Combination of up to 5 cavity wall boxes permissible
- Usable as a device or distributor socket
- Special screwable lid for the connection box

# PYROWIN® CWB

## Fire protection cavity wall boxes

Do you need to install fire protection measures? That is no problem with our retroinstallation sets as you can simply convert the airtight OBO standard cavity wall boxes HG47-L and HG 61-L into fire-safe versions.

European Technical Approval  
ETA-23/0423

The general design certification for  
Germany has been applied for.

	Type	Designation	Version	Item No.
	HG 47-LF	Cavity wall box, airtight, for fire protection walls	Ø 68 mm, H 47 mm	7204320
	HG 61-LF	Cavity wall box, airtight, for fire protection walls	Ø 68 mm, H 61 mm	7204324
	ZH 47-F	Fire protection retroinstallation set for airtight cavity wall box		7204330
	ZH 61-F	Fire protection retroinstallation set for airtight cavity wall box		7204334
	ZH 60-DF	Fire protection lid for cavity wall box		7204340



**OBO Bettermann Holding GmbH & Co. KG**  
P.O. Box 25  
58640 Menden  
GERMANY

**Customer Service**  
Tel.: +49 (0)2373 89-1700  
Fax: +49 (0)2373 89-1238  
export@obo.de

[www.obo-bettermann.com](http://www.obo-bettermann.com)